

## X10 PRO 16 Channel Transceiver PAT02

### Installation and Operating Instructions

The PAT02 Transceiver receives commands from X10 Remote controls and turns on a light or appliance connected to its outlet. The Transceiver also passes the signals onto your house wiring to control lights, appliances, or Wireless Cameras around your home. You plug lights and appliances into X10 Modules (sold separately). You plug Wireless Cameras into Addressable Power Supplies (sold separately).

1. Plug the PAT02 Transceiver into any 120V AC outlet. Fully extend its antenna.
2. Use a dime to set the Housecode dial on the PAT02 to match the X10 modules, cameras, and remote controls you will be using it with.
3. Plug a lamp or appliance into the outlet on the PAT02 (observe the ratings on the back of the PAT02).
4. Press the small button on the PAT02 to test that the lamp/appliance goes on and off.
5. Install 4 AAA alkaline batteries in a PHR03 PalmPad remote control, or CR12A ScanCam remote control (each sold separately).
6. Press 1 ON and OFF on the remote control to control the light/appliance connected to the PAT02.
7. Press the corresponding ON or OFF button on the remote control to turn other X10 Modules or cameras on/off.

### FCC Statement

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: (1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND (2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION. **NOTE:** NO CHANGES OR MODIFICATIONS MAY BE MADE TO THE UNITS. ANY CHANGES MADE TO THE UNITS WILL VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.

**2 YEAR LIMITED WARRANTY x10.com (X10), a division of Authinx Inc., warrants this product to be free from defective material and workmanship for a period of 2 years from the original date of purchase at retail. X10 agrees to repair or replace, at its sole discretion, a defective product if returned to X10 within the warranty period and with proof of purchase. If service is required under this warranty:**

Call 1-888-384-0969, visit [www.x10.com](http://www.x10.com), or email [support@x10.com](mailto:support@x10.com)



### Lamp Module PLM03

Can be Dimmed and Brightened from any X10 Controller. Responds to "All lights on". Rated for 300 W. Incandescent only.

### Appliance Module – PAM01/PAM02

Two pin polarized (PAM01) or 3 pin grounded (PAM02). For controlling an air conditioner, TV, stereo, etc. anywhere in the home. Rated 15A for heaters, coffee pots etc.; 1/3 H.P. for motors; 400W for TVs; 500W for lamps.

### Wall Switch Module PLW01

For controlling important indoor and outdoor security lights. Replaces your existing wall switch and installs like a regular dimmer. Dimmed/brightened from any X10 Controller. Rated 500W incandescent only.

### Split Receptacle Module PAO11

Replaces existing wall outlet. The top outlet functions like an Appliance Module, the bottom one is a regular outlet. Rated 15A.

### 3 - Way Wall Switch Module PLW02

For controlling a light which is controlled by two switches. Same features as WS467.

### Wireless Remote Control System PHK05

Lets you control 16 X10 modules from inside or outside your home. Can also dim and brighten Lamp Modules and Wall Switch Modules. Works with the PHR03 PalmPad Remote and X10 RF Wall Switches (PHW04D)

### Universal Module PUM01

Isolated contact relay and beeper. Can be set for momentary or continuous operation. Not compatible with X10 security systems.

### SocketRocket PSM04

Screws in to an existing light fixture. Controls up to 150W, incandescent only.