



Installation and Operating Instructions for pat03

Wireless remote controls such as the KR19A and PHR04 send wireless Radio Frequency (RF) signals to the pat03 Transceiver. The pat03 then passes the signals onto your house wiring to control lights or appliances around your home. You plug lights and appliances into X10 Modules (sold separately).

1. Plug the pat03 Transceiver into any 120V AC outlet. Fully extend its antenna.
2. Use a dime to set the Housecode dial on the pat03 to match the X10 Modules and remote control you will be using.
3. Set the slide switch on the pat03 to the code you want it to respond to (1 or 9).
4. Plug a lamp or appliance into the outlet on the pat03 (observe the ratings on the back of the pat03).
5. Press the small button on the pat03 to test that the lamp/appliance goes on and off.
6. Press 1 (or 9) ON and OFF on the remote control to control the light/appliance connected to the pat03.
7. Press the corresponding ON or OFF button on the remote control to turn other X10 Modules on/off.
8. You can also turn the light/appliance connected to the pat03 on and off from any X10 plug-in controller. Set the small slide switch on the pat03 to 1 or 9 for it to respond to either of those codes from a plug-in X10 controller.

2 YEAR LIMITED WARRANTY x10.com (X10), a division of Authinx Inc., warrants this product to be free from defective material and workmanship for a period of 2 years from the original date of purchase at retail. X10 agrees to repair or replace, at its sole discretion, a defective product if returned to X10 within the warranty period and with proof of purchase. If service is required under this warranty:

Visit www.x10.com, or email support@x10.com